

7th March 2019

ASX MARKET RELEASE

GOLDEN MILE CONTINUES TO DELIVER MORE HIGH-GRADE GOLD

Additional RC Drilling Results from the Golden Mile Project include:

Falcon Prospect: (Note holes not drilled in numerical or planned order)

- RC drill hole FA18RC019: 2 m @ 12.45 g/t Au (13-15 m)

Shamrock Prospect:

- RC drill hole SH18RC030: 3 m @ 3.24 g/t Au (8-11 m) including 1 m @ 7.79 g/t Au

Following on from the recently reported Falcon and Shamrock RC drilling results including: (Refer ASX release 28th February 2019)

Falcon Prospect: (Note holes not drilled in numerical or planned order)

- RC drill hole FA18RC016: 13 m @ 4.27 g/t Au (44-57 m), including 5 m @ 8.11 g/t Au (48-53 m)
- RC drill hole FA18RC017: 3 m @ 6.91 g/t Au (09-12 m), including 1 m @ 20.20 g/t Au (11-12 m) followed by 5 m @ 1.49 g/t Au (46-51 m)

Shamrock Prospect:

- RC drill hole SH18RC025: 3 m @ 8.18 g/t Au (53-56 m)
- RC drill hole SH18RC026: 1 m @ 6.75 g/t (0-1 m) followed by 3 m @ 3.14 g/t Au (18-21 m)

The Golden Mile project is a Joint Venture (AMG 80% with EXCO 20%) with Exco Resources (QLD) Pty Ltd (EXCO), a 100% subsidiary of Washington H. Soul Pattinson, on the two sub blocks CLON825P & CLON825U from within EPM15923 (Refer ASX release 16th April 2018). The Drilling to date completed by Ausmex continues to deliver shallow, high grade gold results, at depths potentially amenable to a bulk mining operation.

Golden Mile Ore Processing


Under the JV with EXCO, gold ore produced from the Golden Mile JV area will be processed at the 600,000tpa CIP Processing Plant at Round Oak Minerals' Great Australia Mine in Cloncurry, 35 kms NW of the Golden Mile Project. Round Oak Minerals is EXCO's parent company. Stockpiled low-grade ore from historical mining at the AMG owned Mt Freda Gold Mine has been processed at the CIP Processing Plant. The ore was sold to Round Oak Minerals (formerly CopperChem) for \$2.5 m cash in mid-2018. The Golden Mile project, forms part of the Mt Freda Gold Complex. (Refer ASX release 16th April 2018).

Corporate Activity Update

Recent Exploration results discussions with Newcrest Mining Limited regarding the Mt Freda Tier 1 IOCG Complex.

Mt Freda Complex Historic Gold Mines not operated since 1939

"Golden Mile mineralisation"



Significant Drilling Results - Drilling to date

| | | | |
|----------------------|--|----------------------|--------------------|
| Mt Scheelite | 6m @ 3.2g/t Au - including 3m @ 5.5 g/t Au | Mt Scheelite | 15g/t Au |
| Comstock | hole 1: 8m @ 6.32g/t Au including 3m @ 12.1g/t Au | Comstock | 60g/t Au |
| | hole 2: 12m @ 2g/t Au including 3m @ 12.1g/t Au | Falcon | 40.7g/t Au |
| | hole 3: 7m @ 7.6g/t Au including 3m @ 12.1g/t Au | Shamrock | 90g/t Au |
| | hole 4: 9m @ 2.4g/t Au including 4m @ 4.5g/t Au | Golden Relish | no historical data |
| | hole 9: 11m @ 4.39g/t Au including 6m @ 7.4g/t Au | Jewell | no historical data |
| | hole 14: 12m @ 5g/t Au including 4m @ 10g/t Au | Rocket | no historical data |
| | hole 15: 10m @ 4.49g/t Au including 5m @ 6.86g/t Au | Mt Weatherly | 56g/t Au |
| Falcon | hole 1: 8m @ 10.55g/t Au including 4m @ 18.93 | Little Duke | 8.4g/t Au |
| | hole 2: 10m @ 3.78g/t Au including 5m @ 7.23g/t Au | Iron Duke | 9.35g/t Au |
| | hole 3: 3m @ 10.82g/t Au | | |
| | hole 16: 13m @ 4.27g/t Au including 5m @ 8.11g/t Au | | |
| | hole 17: 3m @ 6.91g/t Au including 1m @ 20.2g/t Au, followed by 5m @ 1.49g/t Au | | |
| | hole 19: 2m @ 12.45g/t Au | | |
| Shamrock | hole 1: 28m @ 4.3g/t Au including 2m @ 23.5g/t Au, 2m @ 14.9g/t Au, 2m @ 10.7g/t Au | | |
| | hole 2: 8m @ 2.52g/t Au, 3m @ 27.22g/t Au | | |
| | hole 25: 3m @ 8.18g/t Au | | |
| | hole 26: 1m @ 6.75g/t Au, followed by 3m @ 3.14g/t Au | | |
| | hole 30: 3m @ 3.24g/t Au including 1m @ 7.79g/t Au | | |
| Golden Relish | not yet drilled - to be completed in phase 2 | | |
| Jewell | not yet drilled - to be completed in phase 2 | | |
| Rocket | not yet drilled - to be completed in phase 2 | | |
| Mt Weatherly | not yet drilled - to be completed in phase 2 | | |
| Little Duke | 67m @ 1.33g/t Au and 0.47% Cu. drill hole finished in mineralisation at 132m with the last 5m averaging 1.42g/t Au | | |
| Iron Duke | not yet drilled - to be completed in phase 2 | | |

Refer to ASX releases on 30th August 2018, 10th September 2018, 8th & 26th October 2018, 9th, 15th & 23rd November 2018, & 28th February 2019 for results.

Figure 1. Geological interpretation of the Golden Mile mineralisation and potential Tier 1 igneous host. # Note the Golden Mile high grade drilling results, with multiple high grade, shallow depth intersections.

Ausmex Mining Group (ASX: AMG) (“Ausmex” or “The Company”) is pleased to update shareholders on additional high-grade gold drilling results from the Golden Mile project. Drilling continues to delineate additional shallow, high-grade gold mineralisation. The Company plans to continue to delineate shallow gold mineralisation targeting high grade at shallow depths that may be amenable to a bulk mining operation, with the potential to process any future defined mineral reserves at Round Oak Minerals’ Great Australia Mine 600 Ktpa CIP processing facility in Cloncurry.

Tier 1 IOCG target progress

Brisbane based Geophysical consultants the GeoDiscovery Group Pty Ltd are currently in the final stages of 3D Geophysical modelling of the Mt Freda Complex, aimed at generating a target specific exploration drilling program into the “Canteen” Tier 1 IOCG prospect. Drilling will target massive sulphide copper and gold mineralisation and geological criteria supporting an IOCG-style deposit.

Ausmex controls approximately thirty percent of the “Canteen” IOCG prospect area previously delineated by EXCO in 2012, on ground covered by the Golden Mile JV (between Ausmex and EXCO under which Ausmex holds an 80% interest) and Ausmex’s Mt Freda tenement. Newcrest Mining have a current JV Farm In agreement with EXCO where Newcrest completed drilling in 2018. Exploration results are yet to be released. (Refer ASX:AMG release 19th February 2019).

Corporate Update – Newcrest Mining Limited preliminary exploration results discussions.

Ausmex Managing Director Matt Morgan was recently invited to attend preliminary exploration result discussions with Newcrest Mining Limited senior management representatives in the Newcrest Mining Limited, St Kilda Road offices in Melbourne. Newcrest Mining Limited expressed an interest to review the current Ausmex exploration data set associated with the Mt Freda Complex, including a site inspection, however suitable confidentiality terms were not received from Newcrest, and no further discussions have taken place.

The Company will continue to update shareholders of any further progress relating to Newcrest Mining Limited.




Figure 2. Shamrock and Falcon Prospect drill hole location plan. (Refer to ASX releases on 30th August 2018, 10th September 2018, 8th & 26th October 2018, 9th, 15th & 23rd November 2018, & 28th February 2019 for results).




Figure 3. Falcon X section FA18RC019




Figure 4. Shamrock X section SH18RC030

The Falcon Geology

The reef system consists of lenses of quartz in a soft oxidized formation. The oxidized ore consists of quartz and limonite, with subordinate amounts of calcite, siderite, tourmaline, scheelite, biotite and micaceous hematite. Specimens obtained from the dump show scapolite to be present either in the reef or the adjacent wall rocks. The general strike of the Falcon reef is visibly traceable along abundant workings on surface striking north-south. The reef dips to the West between 75 deg. and vertical along strike. The average gold grade of ore produced from the Falcon reef is recorded by the QLD Government at 40.70 g/t Au.

The Shamrock Geology

The reef workings consist of 3 vertical shafts over a 150 m long north – south striking mineralized zone and a 150 m shallow open cut. The Shamrock reef consists of calcite, quartz and limonite with some scheelite and tourmaline as well as small amounts of magnetite. The reef has an apparent 80 deg. dip to the east. Qld Govt reports that a parcel of ore prior to 1939, was processed and returned almost 3 ounces (90 g/t Au) per tonne. Additional records that state that between 1880 and 1936, the average grade was 40.10 g/t Au. Mining ceased in or around 1939. No exploration has been carried out on these historical mines since closure in 1939.

The Golden Mile

Exploration to date has identified a combined mineralised strike length in excess of 8,000 m, within the 2 km wide zone. The historical mines are located on the western edge of a large Tier 1 IOCG target previously delineated by EXCO in 2012 and drilled under a Joint Venture by Newcrest Mining Limited (ASX:NCM) in 2018.

Exco was listed on the ASX under the code EXS before being acquired by Washington H. Soul Pattinson and Co. Limited (ASX:SOL) in 2012 valuing the company at approximately \$95m. Approximately one third of the Tier 1 IOCG target is situated on Ausmex tenements, (Refer ASX release 27th September 2018).

| Project | Hole ID | From | To | Au (g/t) | Significant Gold |
|----------|-----------|------|----|----------|---|
| SHAMROCK | SH18RC030 | 8 | 9 | 0.93 | 3 m @ 3.24 g/t Au (8-11 m) including 1 m @ 7.79 g/t Au |
| SHAMROCK | SH18RC030 | 9 | 10 | 7.79 | |
| SHAMROCK | SH18RC030 | 10 | 11 | 0.99 | |
| | | | | | |
| FALCON | FA18RC019 | 13 | 14 | 14.7 | 2 m @ 12.45 g/t Au (13-15 m) |
| FALCON | FA18RC019 | 14 | 15 | 10.2 | |

Table 1. Significant drill hole intersections (Note holes not drilled in numerical or planned order)

| Project | Hole ID | Easting | Northing | RL | Dip | Azimuth (Mag) |
|----------|-----------|---------|----------|-----|-----|---------------|
| SHAMROCK | SH18RC030 | 472935 | 7681804 | 262 | -60 | 90 |
| FALCON | FA18RC019 | 472913 | 7681872 | 268 | -60 | 270 |

Table 2. Drill hole collar file

Ends.

For further information, please contact:

Matt Morgan

Managing Director

Ausmex Mining Group Ltd

mattm@ausmexgroup.com.au

Forward Looking Statements

The materials may include forward looking statements. Forward looking statements inherently involve subjective judgement, and analysis and are subject to significant uncertainties, risks, and contingencies, many of which are outside the control of, and may be unknown to, the company.

Actual results and developments may vary materially from that expressed in these materials. The types of uncertainties which are relevant to the company may include, but are not limited to, commodity prices, political uncertainty, changes to the regulatory framework which applies to the business of the company and general economic conditions. Given these uncertainties, readers are cautioned not to place undue reliance on forward looking statements.

Any forward-looking statements in these materials speak only at the date of issue. Subject to any continuing obligations under applicable law or relevant stock exchange listing rules, the company does not undertake any obligation to publicly update or revise any of the forward-looking statements, changes in events, conditions or circumstances on which any statement is based.

Competent Person Statement

Statements contained in this report relating to exploration results and potential are based on information compiled by Mr. Matthew Morgan, who is a member of the Australasian Institute of Mining and Metallurgy (AusIMM). Mr. Morgan is the Managing Director of Ausmex Mining Group Limited and Geologist whom has sufficient relevant experience in relation to the mineralisation styles being reported on to qualify as a Competent Person as defined in the Australian Code for Reporting of Identified Mineral resources and Ore reserves (JORC Code 2012). Mr. Morgan consents to the use of this information in this report in the form and context in which it appears.

Appendices – Table 3. Full assay reporting (Note -1.00 g/t Au = below detection limit)

| Project | Hole ID | From | To | Au (g/t) | Easting | Northing | RL |
|---------|-----------|------|----|----------|----------|-----------|-------|
| FALCON | FA18RC019 | 0 | 1 | 0.01 | 472913.2 | 7681872.4 | 267.4 |
| FALCON | FA18RC019 | 1 | 2 | -1.00 | 472912.7 | 7681872.4 | 266.6 |
| FALCON | FA18RC019 | 2 | 3 | -1.00 | 472912.2 | 7681872.5 | 265.7 |
| FALCON | FA18RC019 | 3 | 4 | 0.01 | 472911.7 | 7681872.5 | 264.8 |
| FALCON | FA18RC019 | 4 | 5 | 0.02 | 472911.2 | 7681872.6 | 264.0 |
| FALCON | FA18RC019 | 5 | 6 | 1.22 | 472910.7 | 7681872.6 | 263.1 |
| FALCON | FA18RC019 | 6 | 7 | 0.02 | 472910.2 | 7681872.7 | 262.2 |
| FALCON | FA18RC019 | 7 | 8 | 0.02 | 472909.7 | 7681872.7 | 261.4 |
| FALCON | FA18RC019 | 8 | 9 | 1.28 | 472909.2 | 7681872.8 | 260.5 |
| FALCON | FA18RC019 | 9 | 10 | 0.56 | 472908.7 | 7681872.8 | 259.6 |
| FALCON | FA18RC019 | 10 | 11 | 0.03 | 472908.2 | 7681872.9 | 258.8 |
| FALCON | FA18RC019 | 11 | 12 | 0.04 | 472907.8 | 7681872.9 | 257.9 |
| FALCON | FA18RC019 | 12 | 13 | 0.13 | 472907.3 | 7681873.0 | 257.0 |
| FALCON | FA18RC019 | 13 | 14 | 14.70 | 472906.8 | 7681873.0 | 256.1 |
| FALCON | FA18RC019 | 14 | 15 | 10.20 | 472906.3 | 7681873.1 | 255.3 |
| FALCON | FA18RC019 | 15 | 16 | 0.12 | 472905.8 | 7681873.2 | 254.4 |
| FALCON | FA18RC019 | 16 | 17 | 0.03 | 472905.3 | 7681873.2 | 253.5 |
| FALCON | FA18RC019 | 17 | 18 | 0.09 | 472904.8 | 7681873.3 | 252.7 |
| FALCON | FA18RC019 | 18 | 19 | 0.06 | 472904.3 | 7681873.3 | 251.8 |
| FALCON | FA18RC019 | 19 | 20 | 0.28 | 472903.8 | 7681873.4 | 250.9 |
| FALCON | FA18RC019 | 20 | 21 | 0.01 | 472903.3 | 7681873.4 | 250.1 |
| FALCON | FA18RC019 | 21 | 22 | 0.03 | 472902.8 | 7681873.5 | 249.2 |
| FALCON | FA18RC019 | 22 | 23 | 0.02 | 472902.3 | 7681873.5 | 248.3 |
| FALCON | FA18RC019 | 23 | 24 | 0.02 | 472901.8 | 7681873.6 | 247.5 |
| FALCON | FA18RC019 | 24 | 25 | 0.03 | 472901.3 | 7681873.6 | 246.6 |
| FALCON | FA18RC019 | 25 | 26 | 0.02 | 472900.9 | 7681873.7 | 245.7 |
| FALCON | FA18RC019 | 26 | 27 | 0.01 | 472900.4 | 7681873.7 | 244.9 |
| FALCON | FA18RC019 | 27 | 28 | 0.01 | 472899.9 | 7681873.8 | 244.0 |
| FALCON | FA18RC019 | 28 | 29 | 0.05 | 472899.4 | 7681873.8 | 243.1 |
| FALCON | FA18RC019 | 29 | 30 | 0.02 | 472898.9 | 7681873.9 | 242.2 |
| FALCON | FA18RC019 | 30 | 31 | 0.01 | 472898.4 | 7681873.9 | 241.4 |
| FALCON | FA18RC019 | 31 | 32 | 0.01 | 472897.9 | 7681874.0 | 240.5 |
| FALCON | FA18RC019 | 32 | 33 | 0.01 | 472897.4 | 7681874.0 | 239.6 |
| FALCON | FA18RC019 | 33 | 34 | 0.01 | 472896.9 | 7681874.1 | 238.8 |
| FALCON | FA18RC019 | 34 | 35 | 0.02 | 472896.4 | 7681874.1 | 237.9 |
| FALCON | FA18RC019 | 35 | 36 | 0.03 | 472896.0 | 7681874.2 | 237.0 |
| FALCON | FA18RC019 | 36 | 37 | 2.58 | 472895.5 | 7681874.2 | 236.1 |
| FALCON | FA18RC019 | 37 | 38 | 0.11 | 472895.0 | 7681874.3 | 235.3 |
| FALCON | FA18RC019 | 38 | 39 | 0.28 | 472894.5 | 7681874.3 | 234.4 |
| FALCON | FA18RC019 | 39 | 40 | 0.02 | 472894.0 | 7681874.4 | 233.5 |
| FALCON | FA18RC019 | 40 | 41 | 0.03 | 472893.5 | 7681874.4 | 232.6 |
| FALCON | FA18RC019 | 41 | 42 | 2.23 | 472893.1 | 7681874.5 | 231.8 |
| FALCON | FA18RC019 | 42 | 43 | 0.07 | 472892.6 | 7681874.5 | 230.9 |
| FALCON | FA18RC019 | 43 | 44 | 0.05 | 472892.1 | 7681874.6 | 230.0 |
| FALCON | FA18RC019 | 44 | 45 | 0.69 | 472891.6 | 7681874.6 | 229.2 |
| FALCON | FA18RC019 | 45 | 46 | 0.17 | 472891.1 | 7681874.7 | 228.3 |
| FALCON | FA18RC019 | 46 | 47 | 0.01 | 472890.6 | 7681874.7 | 227.4 |
| FALCON | FA18RC019 | 47 | 48 | 0.01 | 472890.2 | 7681874.8 | 226.5 |
| FALCON | FA18RC019 | 48 | 49 | 0.01 | 472889.7 | 7681874.8 | 225.7 |
| FALCON | FA18RC019 | 49 | 50 | -1.00 | 472889.2 | 7681874.9 | 224.8 |
| FALCON | FA18RC019 | 50 | 51 | 0.01 | 472888.7 | 7681874.9 | 223.9 |
| FALCON | FA18RC019 | 51 | 52 | -1.00 | 472888.2 | 7681875.0 | 223.0 |
| FALCON | FA18RC019 | 52 | 53 | 0.01 | 472887.7 | 7681875.0 | 222.2 |
| FALCON | FA18RC019 | 53 | 54 | 0.01 | 472887.3 | 7681875.1 | 221.3 |
| FALCON | FA18RC019 | 54 | 55 | 0.01 | 472886.8 | 7681875.1 | 220.4 |
| FALCON | FA18RC019 | 55 | 56 | 0.01 | 472886.3 | 7681875.2 | 219.5 |
| FALCON | FA18RC019 | 56 | 57 | 0.01 | 472885.8 | 7681875.2 | 218.7 |
| FALCON | FA18RC019 | 57 | 58 | -1.00 | 472885.3 | 7681875.3 | 217.8 |
| FALCON | FA18RC019 | 58 | 59 | -1.00 | 472884.8 | 7681875.4 | 216.9 |
| FALCON | FA18RC019 | 59 | 60 | 0.01 | 472884.4 | 7681875.4 | 216.0 |
| FALCON | FA18RC019 | 60 | 61 | 0.02 | 472883.9 | 7681875.5 | 215.2 |

| | | | | | | | |
|----------|-----------|----|----|-------|----------|-----------|-------|
| FALCON | FA18RC019 | 61 | 62 | 0.02 | 472883.4 | 7681875.5 | 214.3 |
| FALCON | FA18RC019 | 62 | 63 | 0.01 | 472882.9 | 7681875.6 | 213.4 |
| FALCON | FA18RC019 | 63 | 64 | 0.04 | 472882.4 | 7681875.6 | 212.5 |
| FALCON | FA18RC019 | 64 | 65 | 0.05 | 472882.0 | 7681875.7 | 211.7 |
| FALCON | FA18RC019 | 65 | 66 | 0.08 | 472881.5 | 7681875.7 | 210.8 |
| FALCON | FA18RC019 | 66 | 67 | 0.03 | 472881.0 | 7681875.8 | 209.9 |
| FALCON | FA18RC019 | 67 | 68 | 0.04 | 472880.5 | 7681875.8 | 209.0 |
| FALCON | FA18RC019 | 68 | 69 | 0.09 | 472880.0 | 7681875.9 | 208.2 |
| FALCON | FA18RC019 | 69 | 70 | 0.03 | 472879.6 | 7681875.9 | 207.3 |
| FALCON | FA18RC019 | 70 | 71 | 0.02 | 472879.1 | 7681876.0 | 206.4 |
| FALCON | FA18RC019 | 71 | 72 | 0.03 | 472878.6 | 7681876.0 | 205.5 |
| SHAMROCK | SH18RC030 | 0 | 1 | 1.02 | 472935.0 | 7681804.2 | 261.6 |
| SHAMROCK | SH18RC030 | 1 | 2 | 0.06 | 472935.5 | 7681804.1 | 260.7 |
| SHAMROCK | SH18RC030 | 2 | 3 | -1.00 | 472935.9 | 7681804.0 | 259.9 |
| SHAMROCK | SH18RC030 | 3 | 4 | 0.01 | 472936.4 | 7681804.0 | 259.0 |
| SHAMROCK | SH18RC030 | 4 | 5 | 0.03 | 472936.9 | 7681803.9 | 258.1 |
| SHAMROCK | SH18RC030 | 5 | 6 | -1.00 | 472937.4 | 7681803.9 | 257.2 |
| SHAMROCK | SH18RC030 | 6 | 7 | -1.00 | 472937.9 | 7681803.8 | 256.4 |
| SHAMROCK | SH18RC030 | 7 | 8 | -1.00 | 472938.4 | 7681803.7 | 255.5 |
| SHAMROCK | SH18RC030 | 8 | 9 | 0.93 | 472938.9 | 7681803.7 | 254.6 |
| SHAMROCK | SH18RC030 | 9 | 10 | 7.79 | 472939.4 | 7681803.6 | 253.8 |
| SHAMROCK | SH18RC030 | 10 | 11 | 0.99 | 472939.8 | 7681803.6 | 252.9 |
| SHAMROCK | SH18RC030 | 11 | 12 | 0.19 | 472940.3 | 7681803.5 | 252.0 |
| SHAMROCK | SH18RC030 | 12 | 13 | 0.23 | 472940.8 | 7681803.4 | 251.1 |
| SHAMROCK | SH18RC030 | 13 | 14 | 0.45 | 472941.3 | 7681803.4 | 250.3 |
| SHAMROCK | SH18RC030 | 14 | 15 | 0.12 | 472941.8 | 7681803.3 | 249.4 |
| SHAMROCK | SH18RC030 | 15 | 16 | -1.00 | 472942.2 | 7681803.2 | 248.5 |
| SHAMROCK | SH18RC030 | 16 | 17 | -1.00 | 472942.7 | 7681803.1 | 247.6 |
| SHAMROCK | SH18RC030 | 17 | 18 | -1.00 | 472943.2 | 7681803.1 | 246.7 |
| SHAMROCK | SH18RC030 | 18 | 19 | -1.00 | 472943.6 | 7681803.0 | 245.9 |
| SHAMROCK | SH18RC030 | 19 | 20 | -1.00 | 472944.1 | 7681802.9 | 245.0 |
| SHAMROCK | SH18RC030 | 20 | 21 | -1.00 | 472944.6 | 7681802.8 | 244.1 |
| SHAMROCK | SH18RC030 | 21 | 22 | -1.00 | 472945.0 | 7681802.8 | 243.2 |
| SHAMROCK | SH18RC030 | 22 | 23 | -1.00 | 472945.5 | 7681802.7 | 242.3 |
| SHAMROCK | SH18RC030 | 23 | 24 | -1.00 | 472946.0 | 7681802.6 | 241.5 |
| SHAMROCK | SH18RC030 | 24 | 25 | -1.00 | 472946.5 | 7681802.5 | 240.6 |
| SHAMROCK | SH18RC030 | 25 | 26 | -1.00 | 472946.9 | 7681802.5 | 239.7 |
| SHAMROCK | SH18RC030 | 26 | 27 | -1.00 | 472947.4 | 7681802.4 | 238.8 |
| SHAMROCK | SH18RC030 | 27 | 28 | -1.00 | 472947.8 | 7681802.3 | 237.9 |
| SHAMROCK | SH18RC030 | 28 | 29 | -1.00 | 472948.3 | 7681802.2 | 237.0 |
| SHAMROCK | SH18RC030 | 29 | 30 | -1.00 | 472948.7 | 7681802.1 | 236.2 |
| SHAMROCK | SH18RC030 | 30 | 31 | -1.00 | 472949.2 | 7681802.0 | 235.3 |
| SHAMROCK | SH18RC030 | 31 | 32 | -1.00 | 472949.6 | 7681801.9 | 234.4 |
| SHAMROCK | SH18RC030 | 32 | 33 | -1.00 | 472950.1 | 7681801.8 | 233.5 |
| SHAMROCK | SH18RC030 | 33 | 34 | -1.00 | 472950.5 | 7681801.7 | 232.6 |
| SHAMROCK | SH18RC030 | 34 | 35 | -1.00 | 472951.0 | 7681801.6 | 231.7 |
| SHAMROCK | SH18RC030 | 35 | 36 | -1.00 | 472951.4 | 7681801.5 | 230.8 |
| SHAMROCK | SH18RC030 | 36 | 37 | -1.00 | 472951.9 | 7681801.4 | 229.9 |

| | | | | | | | |
|----------|-----------|----|----|-------|----------|-----------|-------|
| SHAMROCK | SH18RC030 | 37 | 38 | -1.00 | 472952.3 | 7681801.3 | 229.0 |
| SHAMROCK | SH18RC030 | 38 | 39 | 0.01 | 472952.8 | 7681801.3 | 228.2 |
| SHAMROCK | SH18RC030 | 39 | 40 | -1.00 | 472953.2 | 7681801.1 | 227.3 |
| SHAMROCK | SH18RC030 | 40 | 41 | 0.01 | 472953.6 | 7681801.0 | 226.4 |
| SHAMROCK | SH18RC030 | 41 | 42 | -1.00 | 472954.1 | 7681800.9 | 225.5 |
| SHAMROCK | SH18RC030 | 42 | 43 | -1.00 | 472954.5 | 7681800.8 | 224.6 |
| SHAMROCK | SH18RC030 | 43 | 44 | -1.00 | 472954.9 | 7681800.7 | 223.7 |
| SHAMROCK | SH18RC030 | 44 | 45 | -1.00 | 472955.3 | 7681800.6 | 222.8 |
| SHAMROCK | SH18RC030 | 45 | 46 | -1.00 | 472955.8 | 7681800.5 | 221.9 |
| SHAMROCK | SH18RC030 | 46 | 47 | -1.00 | 472956.2 | 7681800.4 | 221.0 |
| SHAMROCK | SH18RC030 | 47 | 48 | -1.00 | 472956.6 | 7681800.3 | 220.1 |
| SHAMROCK | SH18RC030 | 48 | 49 | -1.00 | 472957.1 | 7681800.2 | 219.2 |
| SHAMROCK | SH18RC030 | 49 | 50 | -1.00 | 472957.5 | 7681800.1 | 218.3 |
| SHAMROCK | SH18RC030 | 50 | 51 | -1.00 | 472957.9 | 7681800.0 | 217.4 |
| SHAMROCK | SH18RC030 | 51 | 52 | -1.00 | 472958.3 | 7681799.8 | 216.5 |
| SHAMROCK | SH18RC030 | 52 | 53 | -1.00 | 472958.8 | 7681799.7 | 215.6 |
| SHAMROCK | SH18RC030 | 53 | 54 | -1.00 | 472959.2 | 7681799.6 | 214.7 |
| SHAMROCK | SH18RC030 | 54 | 55 | -1.00 | 472959.6 | 7681799.5 | 213.8 |
| SHAMROCK | SH18RC030 | 55 | 56 | -1.00 | 472960.0 | 7681799.4 | 212.9 |
| SHAMROCK | SH18RC030 | 56 | 57 | -1.00 | 472960.4 | 7681799.2 | 212.0 |
| SHAMROCK | SH18RC030 | 57 | 58 | -1.00 | 472960.8 | 7681799.1 | 211.1 |
| SHAMROCK | SH18RC030 | 58 | 59 | -1.00 | 472961.2 | 7681799.0 | 210.2 |
| SHAMROCK | SH18RC030 | 59 | 60 | -1.00 | 472961.6 | 7681798.9 | 209.3 |
| SHAMROCK | SH18RC030 | 60 | 61 | -1.00 | 472962.0 | 7681798.7 | 208.4 |
| SHAMROCK | SH18RC030 | 61 | 62 | -1.00 | 472962.4 | 7681798.6 | 207.5 |
| SHAMROCK | SH18RC030 | 62 | 63 | -1.00 | 472962.9 | 7681798.5 | 206.6 |
| SHAMROCK | SH18RC030 | 63 | 64 | -1.00 | 472963.3 | 7681798.4 | 205.7 |
| SHAMROCK | SH18RC030 | 64 | 65 | -1.00 | 472963.7 | 7681798.2 | 204.8 |
| SHAMROCK | SH18RC030 | 65 | 66 | -1.00 | 472964.1 | 7681798.1 | 203.8 |
| SHAMROCK | SH18RC030 | 66 | 67 | -1.00 | 472964.5 | 7681798.0 | 202.9 |
| SHAMROCK | SH18RC030 | 67 | 68 | -1.00 | 472964.9 | 7681797.8 | 202.0 |
| SHAMROCK | SH18RC030 | 68 | 69 | -1.00 | 472965.3 | 7681797.7 | 201.1 |
| SHAMROCK | SH18RC030 | 69 | 70 | 0.01 | 472965.7 | 7681797.6 | 200.2 |
| SHAMROCK | SH18RC030 | 70 | 71 | 0.01 | 472966.1 | 7681797.4 | 199.3 |
| SHAMROCK | SH18RC030 | 71 | 72 | -1.00 | 472966.5 | 7681797.3 | 198.4 |
| SHAMROCK | SH18RC030 | 72 | 73 | -1.00 | 472966.9 | 7681797.2 | 197.5 |
| SHAMROCK | SH18RC030 | 73 | 74 | 0.03 | 472967.3 | 7681797.1 | 196.6 |

JORC Code, 2012 Edition – Table 1 report

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

| Criteria | JORC Code explanation | Commentary |
|-----------------------|--|--|
| Sampling techniques | <ul style="list-style-type: none"> Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases, more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. | <ul style="list-style-type: none"> RC Drilling chip samples recovered via cyclone and splitter Samples were ~2-3kg in weight reverse circulation drilling was used to obtain 1 m samples for targeted ore zones, and 4 m cumulative samples between ore zones from which ~3 kg was pulverised to produce a 30 g charge for ICP analysis for Copper and Cobalt plus Fire Assay for Gold. Samples analysis completed at ALS laboratory QLD |
| Drilling techniques | <ul style="list-style-type: none"> Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc). | <ul style="list-style-type: none"> Reverse Circulation drilling with cyclone and splitter. |
| Drill sample recovery | <ul style="list-style-type: none"> Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. | <ul style="list-style-type: none"> Samples recovered via cyclone and spitter, sample weights indicate representative for 1m. |
| Logging | <ul style="list-style-type: none"> Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and | <ul style="list-style-type: none"> RC chips were geologically logged every 1 m. |

| Criteria | JORC Code explanation | Commentary |
|--|--|---|
| | <p><i>metallurgical studies.</i></p> <ul style="list-style-type: none"> <i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</i> <i>The total length and percentage of the relevant intersections logged.</i> | |
| Sub-sampling techniques and sample preparation | <ul style="list-style-type: none"> <i>If core, whether cut or sawn and whether quarter, half or all core taken.</i> <i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i> <i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i> <i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i> <i>Measures taken to ensure that the sampling is representative of the in-situ material collected, including for instance results for field duplicate/second-half sampling.</i> <i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i> | <ul style="list-style-type: none"> No sub sampling taken from 1 metre RC chips. Field duplicates and standards were entered for analysis with the results indicating that representative sampling and subsequent analysis were completed. |
| Quality of assay data and laboratory tests | <ul style="list-style-type: none"> <i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i> <i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i> <i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</i> | <ul style="list-style-type: none"> Industry standard ICP analysis was completed for Copper and Cobalt plus Fire Assay for Gold samples and subsequent assays Repeat and checks were conducted by ALS laboratories whilst completing the analysis. Standard and duplicates entered by Ausmex The level of accuracy of analysis is considered adequate with no bias samples reported. |
| Verification of sampling and assaying | <ul style="list-style-type: none"> <i>The verification of significant intersections by either independent or alternative company personnel.</i> <i>The use of twinned holes.</i> <i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i> <i>Discuss any adjustment to assay data.</i> | <ul style="list-style-type: none"> Significant intersections inspected and verified by JORC competent personnel No assays were adjusted There were no twinned holes drilled All drill hole logging was completed on site by Geologists, with data entered into field laptop and verified as entered into a geological database Significant intersections for gold |

| Criteria | JORC Code explanation | Commentary |
|--|--|---|
| | | <p>was reported as a combined down hole interval average received assay grade and are not down hole weighted averages.</p> <ul style="list-style-type: none"> As all significant intersections reported for gold were average down hole assays, with no internal waste has been calculated or assumed. |
| <i>Location of data points</i> | <ul style="list-style-type: none"> <i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i> <i>Specification of the grid system used.</i> <i>Quality and adequacy of topographic control.</i> | <ul style="list-style-type: none"> The drill collars have been surveyed by handheld GPS. (accuracy +/- 3m) The drill collars will be surveyed by a permanent base station (accuracy +/- 150mm) and recorded in MGA94, Zone 54 datum |
| <i>Data spacing and distribution</i> | <ul style="list-style-type: none"> <i>Data spacing for reporting of Exploration Results.</i> <i>Whether the data spacing, and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i> <i>Whether sample compositing has been applied.</i> | <ul style="list-style-type: none"> Data spacing, and distribution is NOT sufficient for Mineral Resource estimation No sample compositing has been applied. |
| <i>Orientation of data in relation to geological structure</i> | <ul style="list-style-type: none"> <i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i> <i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i> | <ul style="list-style-type: none"> The orientation of samples is not likely to bias the assay results. |
| <i>Sample security</i> | <ul style="list-style-type: none"> <i>The measures taken to ensure sample security.</i> | <ul style="list-style-type: none"> Samples were taken to Cloncurry by company personnel and despatched by courier to the ALS Laboratory in Townsville |
| <i>Audits or reviews</i> | <ul style="list-style-type: none"> <i>The results of any audits or reviews of sampling techniques and data.</i> | <ul style="list-style-type: none"> No audits or reviews have been undertaken at this stage. |

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

| Criteria | JORC Code explanation | Commentary |
|--|--|---|
| <i>Mineral tenement and land tenure status</i> | <ul style="list-style-type: none"> <i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i> <i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i> | <ul style="list-style-type: none"> ML2718, ML2709, ML2713, ML2719, ML2741 & EPM14163 are owned 100% by Spinifex Mines Pty Ltd. Ausmex Mining Group Limited owns 80% of Spinifex Mines Pty Ltd. Queensland Mining Corporation Limited own 20% of Spinifex Mines. Exploration is completed under an incorporated Joint Venture. 80% beneficial interest in sub blocks CLON825U & CLON825P from EPM15923 & 80/20 JV with CopperChem EPM14475, EPM15858, & EPM18286 are held by QMC Exploration Pty Limited. Ausmex Mining Group Limited owns 80% of QMC Exploration Pty Limited. Queensland Mining Corporation Limited own 20% of Spinifex Mines. Exploration is completed under an incorporated Joint Venture. ML2549, ML2541, ML2517 are 100% owned by Ausmex. |
| <i>Exploration done by other parties</i> | <ul style="list-style-type: none"> <i>Acknowledgment and appraisal of exploration by other parties.</i> | <ul style="list-style-type: none"> All exploration programs conducted by Ausmex Mining Group Limited. Reference to historical mining |
| <i>Geology</i> | <ul style="list-style-type: none"> <i>Deposit type, geological setting and style of mineralisation.</i> | <ul style="list-style-type: none"> ML2718, ML2709, ML2713, ML2719 hosts the Gilded Rose shear hosted quartz reef. There are several golds mineralised hydrothermal quartz reefs within the deposit. ML2741 hosts the shear hosted quartz rich Mt Freda Gold deposit containing Au, Cu, & Co. ML2549, ML2541, ML2517 host copper mineralisation associated with carbonate intrusions into altered mafic host rocks EPM14163 & EPM 15858 contain There are several gold mineralised hydrothermal quartz reefs within the deposit containing Au, Cu, & Co |
| <i>Drill hole Information</i> | <ul style="list-style-type: none"> <i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i> | <ul style="list-style-type: none"> Details within tables within the release |

| Criteria | JORC Code explanation | Commentary |
|---------------------------------|--|--|
| | <ul style="list-style-type: none"> ○ <i>easting and northing of the drill hole collar</i> ○ <i>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</i> ○ <i>dip and azimuth of the hole</i> ○ <i>down hole length and interception depth</i> ○ <i>hole length.</i> • <i>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i> | |
| <i>Data aggregation methods</i> | <ul style="list-style-type: none"> • <i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</i> • <i>Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low-grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i> • <i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i> | <ul style="list-style-type: none"> • Significant average combined down hole assay intersections have been reported as part of this release for Cu & Au. These average intersections are not weighted averages. No weighted down hole averages were reported. • Where Au is <LD, 50% of LD was used for data aggregation i.e. if LD=0.01 then <LD = 0.005 • Significant intersections for all minerals were reported are an average received assay grade for that down hole significant intersection. • The average combined down hole significant intersection did not have an internal Cut-off grade for gold, therefore there was no minimum individual sample cut off, yet only a combined down hole intersection average > 2.0g/t Au. Within these reported Cu intersections there were individual assays < 0.1 G/t Au. • Significant intersections for copper and gold were based on the average grade for the same intersection, as it may be assumed, they represent a combined potential mining unit in the future. • As all significant intersections reported for Copper were a combined total average down hole grade, no internal waste has been calculated or |

| Criteria | JORC Code explanation | Commentary |
|---|--|--|
| | | assumed. |
| <i>Relationship between mineralisation widths and intercept lengths</i> | <ul style="list-style-type: none"> • <i>These relationships are particularly important in the reporting of Exploration Results.</i> • <i>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</i> • <i>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').</i> | <ul style="list-style-type: none"> • No material information is excluded. • intersections have been displayed reported as part of this release. • Interpreted X sections attached to the announcement displaying the geometry of mineralisation |
| <i>Diagrams</i> | <ul style="list-style-type: none"> • <i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</i> | <ul style="list-style-type: none"> • Maps showing the location of the EPMs and MLs are presented in the announcement • Appropriate relevant and labelled X sections attached |
| <i>Balanced reporting</i> | <ul style="list-style-type: none"> • <i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i> | <ul style="list-style-type: none"> • All comprehensive ICP and Fire Assay analytical results for Copper, cobalt and Gold were reported. |
| <i>Other substantive exploration data</i> | <ul style="list-style-type: none"> • <i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i> | <ul style="list-style-type: none"> • Reference to Historical QLD Mines Dept. reports from 1936. • References to previous ASX announcements. |
| <i>Further work</i> | <ul style="list-style-type: none"> • <i>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</i> • <i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i> | <ul style="list-style-type: none"> • Additional mapping, costeans, geophysical surveys, RC and Core drilling |